































Polybatch Material Standard Colors for Molding and Extrusion

Properties	Color	Heat stability ISO 12877-2	Light fastness ISO 4892-2	Weather Fastness ISO 4892-2	NIR Detectable	Specific Property Features	
<ul style="list-style-type: none"> Heat stability refers to 2% masterbatch addition in the respective carrier resin (ISO 12877-2, maximum color change of 4 according to Grey Scale ISO 105-A02, 5 minute dwell time) Light fastness refers to 2% masterbatch addition in the respective carrier resin (ISO 4892-2, measured according to Blue Wool Scale ISO 102-B02, 8 = very good, 1 = very poor) Weather fastness refers to 2% masterbatch addition in the respective carrier resin (ISO 4892-2, measured according to Grey Scale ISO 102-A02, 5 = very good, 1 = very poor) NIR Detectable refers to 2% masterbatch addition in the respective carrier resin (internal method, polymer identification by near infrared spectroscopy) Food contact - detailed information available on request 							
Standard Colors for Polyolefins - Based on polyethylene carrier resin							
Polybatch L 2546		Yellow	300°C	6	2	Yes	
Polybatch L 1014		Orange	290°C	7-8	1-2	Yes	
Polybatch 5020		Red	240°C	2-3	0-1	Yes	
Polybatch L 5646		Red	300°C	8	4	Yes	
Polybatch 5330		Red	240°C	6	1	Yes	
Polybatch 5500		Red	240°C	5-6	1	Yes	
Polybatch 5505		Red	240°C	5-6	1	Yes	
Polybatch 5670		Red	240°C	6	1	Yes	
Polybatch 5246		Pink	260°C	6-7	1	Yes	
Polybatch 4022		Violet	240°C	6	2-3	Yes	
Polybatch 4300		Blue	280°C	8	5	Yes	
Polybatch 4012		Blue	290°C	8	4-5	Yes	
Polybatch L 4535		Blue	290°C	8	4-5	Yes	
Polybatch 4020		Blue	290°C	8	5	Yes	Transparent blue for tint
Polybatch 4021		Blue	300°C	8	4-5	Yes	

You can find out more about us by visiting our website at: www.lyondellbasell.com

Before using a LyondellBasell product, customers and other users should make their own independent determination that the product is suitable for the intended use. They should also ensure that they can use the LyondellBasell product safely and legally. (Material Safety Data Sheets are available from LyondellBasell at www.lyondellbasell.com) This document does not constitute a warranty, express or implied, including a warranty of merchantability or fitness for a particular purpose. No one is authorized to make such warranties or assume any liabilities on behalf of LyondellBasell except in writing signed by an authorized LyondellBasell employee. Unless otherwise agreed in writing, the exclusive remedy for all claims is replacement of the product or refund of the purchase price at LyondellBasell's option, and in no event shall LyondellBasell be liable for special, consequential, punitive, or exemplary damages. Polybatch, Polyblak and Polywhite are trademarks owned and/or used by the LyondellBasell family of companies. Polybatch and Polyblak are registered in the U.S. Patent and Trademark Office.















Polybatch Material Standard Colors for Molding and Extrusion

Properties	Color	Heat stability ISO 12877-2	Light fastness ISO 4892-2	Weather Fastness ISO 4892-2	NIR Detectable	Specific Property Features	
<ul style="list-style-type: none"> Heat stability refers to 2% masterbatch addition in the respective carrier resin (ISO 12877-2, maximum color change of 4 according to Grey Scale ISO 105-A02, 5 minute dwell time) Light fastness refers to 2% masterbatch addition in the respective carrier resin (ISO 4892-2, measured according to Blue Wool Scale ISO 102-B02, 8 = very good, 1 = very poor) Weather fastness refers to 2% masterbatch addition in the respective carrier resin (ISO 4892-2, measured according to Grey Scale ISO 102-A02, 5 = very good, 1 = very poor) NIR Detectable refers to 2% masterbatch addition in the respective carrier resin (internal method, polymer identification by near infrared spectroscopy) Food contact - detailed information available on request 							
Polybatch 4025		Blue	300°C	8	4-5	Yes	
Polybatch 4500		Blue	300°C	8	4-5	Yes	Transparent blue for tint
Polybatch 4656/5		Blue	300°C	8	5	Yes	
Polybatch 4358		Blue	290°C	8	5	Yes	
Polybatch 3000		Green	300°C	8	5	Yes	
Polybatch L 3116		Green	250°C	7	2-3	Yes	
Polybatch L 3060		Green	250°C	7-8	4-5	Yes	
Polybatch 3015		Green	300°C	8	5	Yes	Transparent green for tint
Polybatch L 3888		Green	300°C	8	5	No	
Polybatch 9600		Ivory	300°C	8	5	Yes	
Polybatch 9035		Ivory	300°C	8	5	Yes	
Polybatch 6027		Beige	250°C	7-8	4	Yes	
Polybatch 1266		Beige	250°C	7-8	4	Yes	
Polybatch 1340		Brown	300°C	8	5	Yes	
Polybatch 1281		Brown	300°C	8	5	No	

You can find out more about us by visiting our website at: www.lyondellbasell.com

Before using a LyondellBasell product, customers and other users should make their own independent determination that the product is suitable for the intended use. They should also ensure that they can use the LyondellBasell product safely and legally. (Material Safety Data Sheets are available from LyondellBasell at www.lyondellbasell.com) This document does not constitute a warranty, express or implied, including a warranty of merchantability or fitness for a particular purpose. No one is authorized to make such warranties or assume any liabilities on behalf of LyondellBasell except in writing signed by an authorized LyondellBasell employee. Unless otherwise agreed in writing, the exclusive remedy for all claims is replacement of the product or refund of the purchase price at LyondellBasell's option, and in no event shall LyondellBasell be liable for special, consequential, punitive, or exemplary damages. Polybatch, Polyblak and Polywhite are trademarks owned and/or used by the LyondellBasell family of companies. Polybatch and Polyblak are registered in the U.S. Patent and Trademark Office.















Polybatch Material Standard Colors for Molding and Extrusion

Properties	Color	Heat stability ISO 12877-2	Light fastness ISO 4892-2	Weather Fastness ISO 4892-2	NIR Detectable	Specific Property Features	
<ul style="list-style-type: none"> Heat stability refers to 2% masterbatch addition in the respective carrier resin (ISO 12877-2, maximum color change of 4 according to Grey Scale ISO 105-A02, 5 minute dwell time) Light fastness refers to 2% masterbatch addition in the respective carrier resin (ISO 4892-2, measured according to Blue Wool Scale ISO 102-B02, 8 = very good, 1 = very poor) Weather fastness refers to 2% masterbatch addition in the respective carrier resin (ISO 4892-2, measured according to Grey Scale ISO 102-A02, 5 = very good, 1 = very poor) NIR Detectable refers to 2% masterbatch addition in the respective carrier resin (internal method, polymer identification by near infrared spectroscopy) Food contact - detailed information available on request 							
Polybatch 1028		Brown	300°C	8	5	No	
Polybatch 8760		Grey	300°C	8	5	Yes	
Polybatch 8899		Grey	300°C	8	5	Yes	
Polybatch 8035		Grey	300°C	8	5	Yes	
Polybatch 8368		Grey	300°C	8	5	No	
Polybatch 8218		Grey	300°C	8	5	No	
Polybatch 7030		Silver	300°C	8	5	No	Metallic Silver
Polybatch 7010		Blue	300°C	8	5	No	Metallic Blue
Polybatch 7012		Green	300°C	8	5	No	Metallic Green
Polybatch 73641 NIR		Black	300°C	8	5	Yes	NIR detectable alternative to carbon black
Polyblak 1423/20		Black	300°C	8	5	No	Carbon black, P-type
Polyblak 1850		Black	300°C	8	5	No	Carbon black, blue-tone, no food contact
Polywhite 8000		White	300°C	8	5	Yes	TiO ₂ , neutral undertone
Polywhite 8160		White	300°C	8	5	Yes	TiO ₂ , blue undertone

You can find out more about us by visiting our website at: www.lyondellbasell.com

Before using a LyondellBasell product, customers and other users should make their own independent determination that the product is suitable for the intended use. They should also ensure that they can use the LyondellBasell product safely and legally. (Material Safety Data Sheets are available from LyondellBasell at www.lyondellbasell.com) This document does not constitute a warranty, express or implied, including a warranty of merchantability or fitness for a particular purpose. No one is authorized to make such warranties or assume any liabilities on behalf of LyondellBasell except in writing signed by an authorized LyondellBasell employee. Unless otherwise agreed in writing, the exclusive remedy for all claims is replacement of the product or refund of the purchase price at LyondellBasell's option, and in no event shall LyondellBasell be liable for special, consequential, punitive, or exemplary damages. *Polybatch*, *Polyblak* and *Polywhite* are trademarks owned and/or used by the LyondellBasell family of companies. *Polybatch* and *Polyblak* are registered in the U.S. Patent and Trademark Office.

Polybatch Material Standard Colors for Molding and Extrusion

Properties	Color	Heat stability ISO 12877-2	Light fastness ISO 4892-2	Weather Fastness ISO 4892-2	NIR Detectable	Specific Property Features	
<ul style="list-style-type: none"> Heat stability refers to 2% masterbatch addition in the respective carrier resin (ISO 12877-2, maximum color change of 4 according to Grey Scale ISO 105-A02, 5 minute dwell time) Light fastness refers to 2% masterbatch addition in the respective carrier resin (ISO 4892-2, measured according to Blue Wool Scale ISO 102-B02, 8 = very good, 1 = very poor) Weather fastness refers to 2% masterbatch addition in the respective carrier resin (ISO 4892-2, measured according to Grey Scale ISO 102-A02, 5 = very good, 1 = very poor) NIR Detectable refers to 2% masterbatch addition in the respective carrier resin (internal method, polymer identification by near infrared spectroscopy) Food contact - detailed information available on request 							
Standard Colors for Polystyrene - based on polystyrene carrier resin							
Polybatch HS 2503/2		Yellow	250°C	5	-	Yes	
Polybatch HS 5005/2		Red	250°C	3-4	-	Yes	
Polybatch HS 5510/2		Red	250°C	3-4	-	Yes	
Polybatch HS 4005		Blue	280°C	6	-	Yes	
Polybatch HS 1001/2		Brown	300°C	8	-	Yes	
Polybatch HS 7277		Silver	280°C	8	-	No	Metallic Silver
Polybatch PS 73647 NIR		Black	300°C	7	-	Yes	NIR detectable alternative to carbon black
Polyblak SB-3278		Black	300°C	8	-	No	Carbon black, high tint strength
Polyblak HS 7110		Black	300°C	8	-	No	Carbon black, high jetness
Polywhite HS 8952		White	300°C	8	-	Yes	TiO ₂ , blue undertone
Standard Colors for PET - based on PET carrier resin							
Polybatch PET 73646 NIR		Black	290°C	7	-	Yes	NIR detectable alternative to carbon black
Polywhite PT 8187		White	300°C	8	-	Yes	TiO ₂ , neutral undertone
Standard Colors for Polyamide - based on PA-6 carrier resin							
Polywhite PA 85848 VEG		White	300°C	8	-	Yes	TiO ₂ , neutral undertone
Standard Colors for PLA - based on PLA carrier resin							
Polywhite PLA 8757		White	230°C	8	-	Yes	TiO ₂ , neutral undertone

You can find out more about us by visiting our website at: www.lyondellbasell.com

Before using a LyondellBasell product, customers and other users should make their own independent determination that the product is suitable for the intended use. They should also ensure that they can use the LyondellBasell product safely and legally. (Material Safety Data Sheets are available from LyondellBasell at www.lyondellbasell.com) This document does not constitute a warranty, express or implied, including a warranty of merchantability or fitness for a particular purpose. No one is authorized to make such warranties or assume any liabilities on behalf of LyondellBasell except in writing signed by an authorized LyondellBasell employee. Unless otherwise agreed in writing, the exclusive remedy for all claims is replacement of the product or refund of the purchase price at LyondellBasell's option, and in no event shall LyondellBasell be liable for special, consequential, punitive, or exemplary damages. Polybatch is a trademark owned or used by LyondellBasell group companies and are registered in the U.S. Patent and Trademark Office.